



SPECIFICATION			
Model NO.	DLE-SM200IP	DLE-IM200IP	DLE-IHD200IP
<b>Camera</b>			
Image Sensor	1/2.7" Smartsens CMOS	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	1/2.8" SONY Starvis Back-illuminated Low-light CMOS Sensor
Minimum Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on	0.001Lux@F1.2(AGC ON), 0Lux IR on	0.001Lux@F1.2(AGC ON), 0Lux IR on
Main Stream	1080P@25fps, 720P@30fps	1080P@25fps, 720P@30fps	30fps@2MP(1920x1080P)/720P
Effective Pixels	1936(H)*1096(V)	1945(H)*1097(V)	1945(H)*1097(V)
Resolution	2MP 1080P		
Compression	H.264/H.265		
TV System	PAL/NTSC		
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec		
S/N Ratio	≥52dB		
Scanning System	Progressive		
Video Output	Network		
Reset Button	Optional		
<b>Lens</b>			
Focus Length	3.6mm		
Focus Control	Fixed		
Lens Type	Fixed		
Pixels	2MP 1080P		
<b>Night Vision</b>			
Infrared LED	18PCS SMD IR Leds		
Infrared Distance	30M		
IR Status	Auto Control		
IR Power On	Auto Control		
<b>Network</b>			
Ethernet	RJ-45 (10/100Base-T)		
Wireless	/		

Protocol	RTSP/DHCP/NTP/DST/FTP/SMTP
ONVIF	ONVIF 17.06 compatible
P2P	YES, Support QR Code
POE	Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)
Smart Phone	iPhone, iPad, Android, Android Pad
<b>Camera Features</b>	
Image Config	Privacy Mask, Flip, Mirror
Day/Night	Color/ B&W (IR-CUT )
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Android/IOS
<b>General</b>	
Housing	Metal , IP66
Anti-cut Bracket	Optional
IR Cut Filter	YES
Operation Temperature	-30℃ ~ +60℃ RH90% Max
Storage Temperature	-30℃ ~ +60℃ RH90% Max
Power Source	DC12V±10%, 950mA
Dimension	127(W) x 105(H)
Weight	750g