



SPECIFICATION	
Model	PTBLW-IH200IP-4X
<b>Camera</b>	
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor, Hisilicon Hi3516C
Focus Length	f=2.8mm-12mm
Focus Control	4X Optical Zoom
Output pixel	1080P@30fps
Horizontal Resolution	2MP
Compression	H.265/H.264
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~200°
Tilt Rotation Speed	25°/s
Tilt Rotation Range	-45°~40°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Night Vision</b>	
Infrared LED	42μx6PCS IR LEDS
IR Range	60M
Day-night mode	AUTO
<b>Network</b>	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Stream type	Main Stream / Sub Stream / MJPEG
<b>Interface</b>	
SD Card	Optional
POE	Optional

<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	38.5x17.5x14(cm)
Weight	3Kgs